

## SECTION 13 - MECHANICAL

| <u>Part</u>                         | <u>C</u> | <u>Type &amp; Subject</u>  | <u>Pages</u> | <u>Status</u>   |
|-------------------------------------|----------|--|--------------|-----------------|
| <u>13.1 General Recommendations</u> |          |  |              |                 |
| 13.1.5                              | 37-2     | Recommended Design Criteria for One-Inch Welded Steel Pipe, Couplings, Plugs and Rivets                    | 3            | Reaffirmed 2006 |
| 13.1.6                              | 37-2     | Recommended Design Criteria for One-Inch Signal Pipe and Coupling, Details & Assemblies                    | 2            | Reaffirmed 2006 |
| 13.1.10                             | 37-2     | Recommended Design Criteria for Pipe Adjusting Screws, Details & Assemblies                                | 2            | Reaffirmed 2005 |
| 13.1.15                             | 37-2     | Recommended Design Criteria for Screw and Solid Jaws, Details  | 2            | Reaffirmed 2005 |
| 13.1.20                             | 37-2     | Recommended Design Criteria for Solid Jaws With Tang Ends, Assemblies                                      | 1            | Reaffirmed 2005 |
| 13.1.21                             | 37-2     | Recommended Design Criteria for Jaws With Tang Ends, Plain Ends and Adjustable Links, Details & Assemblies | 2            | Reaffirmed 2005 |
| 13.1.25                             | 37-2     | Recommended Design Criteria for Pipe-Line Insulation for One-Inch Pipe, Details & Assemblies               | 2            | Reaffirmed 2006 |
| 13.1.30                             | 37-2     | Recommended Design Criteria for Tang End With Screw Jaw, Details & Assemblies                              | 1            | Reaffirmed 2006 |

## SECTION 13 - MECHANICAL (Cont'd)

| <u>Part</u> | <u>C</u> | <u>Type &amp; Subject</u>  | <u>Pages</u> | <u>Status</u>   |
|-------------|----------|--|--------------|-----------------|
| 13.1.31     | 37-2     | Recommended Design Criteria for Double Tang End, Details & Assembly                        | 1            | Reaffirmed 2006 |
| 13.1.35     | 37-2     | Recommended Design Criteria for One-Way Horizontal Crank Stand Assembly                    | 1            | Reaffirmed 2006 |
| 13.1.38     | 37-2     | Recommended Design Criteria for Crank, Details   | 2            | Revised 2005    |
| 13.1.39     | 37-2     | Recommended Design Criteria for One-Way Horizontal Crank Stand, Details                    | 2            | Revised 2005    |
| 13.1.45     | 37-2     | Recommended Design Criteria for One-Way Horizontal Pipe Compensator, Details & Assembly    | 2            | Revised 2005    |
| 13.1.46     | 37-2     | Recommended Design Criteria for Pipe Compensator Crank, Details                            | 2            | Revised 2005    |
| 13.1.47     | 37-2     | Recommended Design Criteria for Tang End With Lug and Compensator Link, Details & Assembly | 2            | Reaffirmed 2005 |
| 13.1.50     | 37-2     | Recommended Design Criteria for Crank and Jaw Pins   | 1            | Reaffirmed 2005 |
| 13.1.57     | 37-2     | Recommended Design Criteria for One-Way Pipe Carriers, Details & Assembly                  | 2            | Reaffirmed 2005 |